

POWERED BY

somfy®

THE **BRADLEY**
COLLECTION

TECHNICAL GUIDE

TECHNICAL GUIDE

This technical guide has been designed to be used alongside our ⚡|Electric collections specification guides.

If you have any questions, please contact your local sales representative or The Bradley Collection directly.



Electrical installations must be carried out by qualified professionals, in accordance with the relevant wiring diagrams and local regulations.

Track Configurations Page 3-8

PROFILE Page 4

⚡|ELECTRIC Page 5-7

HAND DRAWN Page 8

Curtain Information Page 9-16

Motors Page 17-22

Controls Page 23-27

Systems are manufactured to suit individual requirements. When calculating the length of your system, remember to allow sufficient tolerance beyond the width of the frame to enable curtains to fully draw back to the edge of the window.

Systems exceeding the recommended maximum distance between brackets will be supplied in equal sections unless otherwise specified. Joiners will be included, and joining brackets should be installed at each joint.




Motor Type	Maximum system length	Maximum system length
	<i>Single Stack ▶</i>	<i>Pair Stack ▶◀</i>
Glydea Ultra 60e	12000mm (39')	12000mm (39')
Iriso 45WF	10000mm (32.5')	10000mm (32.5')
Movelite 35	10000mm (32.5')	10000mm (32.5')
Movelite 35WF	6000mm (20')	6000mm (20')

HAND DRAWN


For windows or double treatments where motorisation is not required, hand drawn options are available.

ROLLERS

Systems ordered with Standard Rollers will be supplied as per the diagrams below.




SINGLE STACK ▶




Supplied with 1x Overlap Arm. 1x Hook Point.

PAIR STACK ▶◀




Supplied with 2x Overlap Arm. 2x Hook Point.


 For Specification info on Overlap arms and Hook Points see page 14.

RIPPLE ROLLERS

Systems ordered with Ripple Rollers will be supplied as per the diagrams below.




SINGLE STACK ▶



Supplied with 1x Ripple Arm. 1x Ripple Hook Point.

PAIR STACK ▶◀




Supplied with 2x Ripple Butt Arm. 2x Ripple Hook Point.




For Specification info on Ripple arms and Hook Points see page 15

RIPPLEFOLD® ROLLERS

Systems ordered with Ripplefold® Rollers will be supplied as per the diagrams below.




SINGLE STACK ▶



Supplied with 1x Ripplefold® Arm. 1x Ripplefold® Hook Point.


PAIR STACK ▶◀




Supplied with 2x Ripplefold® Butt Arm. 2x Ripplefold® Hook Point.

ROLLERS


Systems ordered with Rollers will be supplied as per the diagrams below.



SINGLE STACK ▶



PAIR STACK ▶◀




RIPPLE ROLLERS


Systems ordered with Rollers will be supplied as per the diagrams below.



SINGLE STACK ▶




PAIR STACK ▶◀




RIPPLEFOLD® ROLLERS


Systems ordered with Ripplefold Rollers will be supplied as per the diagrams below.



SINGLE STACK ▶



PAIR STACK ▶◀




STACKING OPTIONS

For electric systems, stacking configuration must be specified at the point of order, as it is set during assembly.

Ripple & Ripplefold® curtains require stack type (*single or pair*) to be confirmed when ordering, as this determines the number of rollers supplied.

SINGLE MOTOR - Single Stack ▶

On single stack systems the motor is always positioned on the stacking side. Allowing the motor to be hidden behind the curtain.



SINGLE MOTOR - Pair Stack ▶◀

Pair stack curtains can have the motor positioned at either end of the system. Curtains must be equal in length



STACK SIZES

The stack area is the space where curtains gather when fully open. Positioning the stack over the wall, rather than the glazing, allows more natural light into the room during the day. As a guideline, allow approximately 30% of the track length for curtain stacking. Fuller curtain styles (e.g. pencil pleat) and lined or interlined fabrics will require additional space.

SINGLE STACK ▶



PAIR STACK ▶◀



STANDARD HEADINGS

Standard rollers will be supplied every 100mm (4") unless otherwise specified.


Rollers can be loaded and removed from either end of the track after assembly by removal of the spring stop or return cover as shown.



ROLLERS

Rollers are preferred for heavy drapery.
One roller is specified for every 100mm (4").

STANDARD
Fullness 1.5





PINCH PLEAT
Fullness 2.0



RIPPLE HEADING

Ripple is a simple **S** folded heading system consisting of rollers spaced by a cord and a special pocketed header tape that is sewn onto a flat panel curtain. When assembled in the track, the rollers on the cord are spaced at distance shown below and this fixes the 'pitch' of the ripple. The flat panel curtain(s) are made in the conventional way with the pocketed header tape sewn to the header. Hooks are fitted to header tape at a set spacing creating the ripple effect

RIPPLE



RIPPLE ROLLERS

80mm (3 1/8") spacing between the rollers.

Roller-Cord Spacing	Curtain Hook Spacing	Approx. Curtain Fullness	Stack Depth <i>per 1M (39 1/8") of track</i>	Min Bracket Projection
60mm (2 3/8")	120mm (4 7/8")	2.3	270mm (10 5/8")	100mm (4")
80mm (3 1/8")	160mm (6 5/16")	2.3	180mm (7 1/16")	100mm (4")



RIPPLEFOLD® HEADING

Ripplefold® is named for the soft, consistent wave pattern formed as the drapery hangs from the track, offering a clean and contemporary aesthetic.

Drapery is constructed using snap tape (Graber® required), allowing it to attach directly to the auxiliary carriers within the track.

Fullness is determined by carrier spacing. Higher fullness factors create a more luxurious appearance. Lutron® Ripplefold® systems are available in three fullness options.

RIPPLEFOLD®



RIPPLEFOLD® ROLLERS

80% • 100% • 120% Fullness options

	Roller-Cord Spacing	Curtain Fullness	Stack Depth <i>per 1M (39 1/8") of track</i>	Min Bracket Projection
	60mm (2 3/8")	80%	270mm (10 5/8")	100mm (4")
	55mm (2 1/16")	100%	310mm (12 3/16")	100mm (4")
	45mm (1 3/4")	120%	360mm (14 3/16")	100mm (4")


Different types of fabric have widely differing weights. The type of curtain heading used (see below) will determine the fullness of the fabric used: this can be anything from 1.5 x the width of the track to 3.0 x track width.

The chart below assumes 100% fullness (2.0 x width of the track) the weights are approximate values and can vary for many reasons. Always check the expected and final total curtain weight with the curtain maker. Based on 1200mm (48") fabric width

Curtain Type	Width↔/Drop↕	1m (3.5')	2m (7')	3m (10.5')	4m (14")	5m (16.5')	6m (20")
Print Cotton <i>(Light)</i>	1m (3.5')	0.8kg (1.8lb)	1.7kg (3.7lb)	2.5kg (5.5lb)	3.4kg (7.4lb)	4.2kg (9.2lb)	5.0kg (11.1lb)
	2m (7')	1.3kg (2.8lb)	2.5kg (5.5lb)	3.8kg (8.3lb)	5kg (11.1lb)	6.3kg (13.9lb)	7.6kg (16.6lb)
	3m (10')	1.7kg (3.7lb)	3.4kg (7.4lb)	5kg (11.1lb)	6.7kg (14.8lb)	8.4kg (18.5lb)	10kg (22lb)
Linen <i>(Medium)</i>	1m (3.5')	1.1kg (2.3lb)	2.1kg (4.6lb)	3.2kg (6.9lb)	4.2kg (9.2lb)	5.3kg (11.6lb)	6.3kg (13.9lb)
	2m (7')	1.6kg (3.5lb)	3.2kg (6.9lb)	4.7kg (10.4lb)	6.3kg (13.9lb)	7.9kg (17.3lb)	9.5kg (20.8lb)
	3m (10')	2.1kg (4.6lb)	4.2kg (9.2lb)	6.3kg (13.9lb)	8.4kg (18.5lb)	10.5kg (23.1lb)	12.6kg (27.7lb)
Velvet <i>(Heavy)</i>	1m (3.5')	1.5kg (3.2lb)	3.2kg (6.5lb)	4.4kg (9.7lb)	5.9kg (12.9lb)	7.4kg (16.2lb)	8.8kg (19.4lb)
	2m (7')	2.2kg (4.9lb)	4.4kg (9.7lb)	6.7kg (12.6lb)	8.8kg (19.4lb)	11kg (24.3lb)	13.2kg (22lb)
	3m (10')	2.9kg (6.5lb)	5.9kg (12.9lb)	8.8kg (19.4lb)	11.8kg (26lb)	14.7kg (32.2lb)	17.6kg (39lb)


Maximum weight recommendations for all standard curtain types using roller are defined to ensure safe and proper function of the electric system. These must be adhered to. See table below for details of all options.

ROLLERS




One roller is specified for every 100mm (4")

RIPPLE ROLLERS



Rollers spacing options
80mm (3 1/8")

RIPPLEFOLD® ROLLERS



Fullness options
80% • 100% • 120%
(for roller spacing see page 10)

! Bends will considerably reduce the load bearing capability of any system.

⚡ GLYDEA ULTRA 60E MOTOR WT • RTS

System Width <i>Single Stack ▶ / Pair Stack ▶◀</i>	Straight	1 Bend Bay	2 Bend Bay	4 Bend Bay	Curved Bay
3m (10')	60kg (132lb)	45kg (99lb)	35kg (77lb)	4 BEND BAYS REQUIRE 2X 2 BEND BAY SYSTEMS	35kg (77lb)
6m (19.5')	60kg (132lb)	45kg (99lb)	35kg (77lb)		35kg (77lb)
10m (33') <i>[Curve Max 8m (26')]</i>	60kg (132lb)	45kg (99lb)	25kg (55lb)		[25kg (55lb)]
12m (39')	55kg (121.2lb)	35kg (77lb)	—		—

🔋 IRISMO 45 WF MOTOR RTS

System Width <i>Single Stack ▶ / Pair Stack ▶◀</i>	Straight	1 Bend Bay	2 Bend Bay	4 Bend Bay	Curved Bay
3m (10')	45kg (99lb)	45kg (99lb)	35kg (77lb)	4 BEND BAYS REQUIRE 2X 2 BEND BAY SYSTEMS	35kg (77lb)
6m (19.5')	45kg (99lb)	45kg (99lb)	30kg (66lb)		10kg (22lb)
10m (33')	45kg (99lb)	35kg (77lb)	20kg (44lb)		—


⚡ MOVELITE 35 MOTOR WT • RTS

System Width <i>Single Stack ▶ / Pair Stack ▶◀</i>	Straight	1 Bend Bay	2 Bend Bay	4 Bend Bay	Curved Bay
3m (10')	35kg (77lb)	35kg (77lb)	15kg (33lb)	4 BEND BAYS REQUIRE 2X 2 BEND BAY SYSTEMS	35kg (77lb)
6m (19.5')	35kg (77lb)	25kg (55lb)	10kg (22lb)		10kg (22lb)
10m (33')	35kg (77lb)	20kg (44lb)	—		—


🔋 MOVELITE 35 WF MOTOR RTS

System Width <i>Single Stack ▶ / Pair Stack ▶◀</i>	Straight	1 Bend Bay	2 Bend Bay	4 Bend Bay	Curved Bay
3m (10')	60kg (132lb)	! UNSUITABLE FOR USE WITH BENT OR CURVED TRACKS			
6m (19.5')	60kg (132lb)				




STANDARD OVERLAP ARM




Supplied as standard on Single & Pair Stack Systems with Rollers






RIPPLE ARM - Single Stack ▶



Supplied on single stack systems with Ripple Rollers






RIPPLE BUTT ARM - Pair Stack ▶◀




Supplied on pair stack systems with Ripple Rollers




RIPPLEFOLD® ARM - Single Stack ▶



Supplied on single stack systems with Ripplefold® Rollers



RIPPLEFOLD® BUTT ARM - Pair Stack ▶◀



Supplied on pair stack systems with Ripplefold® Rollers


The mains-powered motor must be positioned on the same side of the window as the power supply.

Wiring diagrams are available upon request.


Motorised systems are unsuitable for use outdoors or in damp environments such as shower rooms and bathrooms.

MOTOR POSITIONING


⚡ MAINS POWERED SYSTEMS



🔋 BATTERY POWERED SYSTEMS SOMFY® MOVELITE & IRISMO ONLY



LEFT HAND MOTOR



RIGHT HAND MOTOR



⚡ GLYDEA ULTRA 60E MOTOR WT • RTS

Size L291mm (11 7/16") x w93mm (3 11/16") x D53mm (2 1/16")
Power Supply 120V, 50/60Hz
Noise < 38 dBA in Silent mode
Max Length 11m (36')
Max Weight 60kg (132lb)
Control WT, RTS , Zigbee 3.0 (via module)

WT Motor
 4 core cable
 Mains switching
 Controlled with automation systems or hard wired wall switch

RTS Motor
 3 core cable
 Built in radio receiver
 Dry contact, Volt free switching
 Controlled with Somfy remote or app control options / automation systems via volt free or RTS / volt free hard wired wall switch
 Compatible with Situo remote controls and TaHoma Switch

Zigbee 3.0 Module available, Compatible with Ysia remote controls and TaHoma Switch



MOTOR FEATURES	Glydea Ultra 60e WT	Glydea Ultra 60e RTS
Soft Start	✓	✓
Soft Stop	✗	✓
Intermediate Position	✗	✓
Manual Override	✓	✓
Touch Motion	✗	✓
Automatic Limits on End Stop	✓	✓
Back Release	✓	✗
Adjustable Limits	✗	✓
Speed Control & Adjustment	✓	✓
Set via 3 NO Dry Contact Setting tool	✓	✓
Setting with button on motor	✓	✓
Motor direction change	✓	✓
DCT ergonomics setting 2 or 3 buttons	✗	✓
Factory reset	✓	✓
LED indicators	✓	✓
Modulability	✗	✓
Silent mode	✓	✓
Buzzer indicators	✗	✗
Remote control	✗	✓
App control	✗	✓
Zigbee Integration	✓	✓

IRISMO 45 WF MOTOR RTS

Size	L308mm (12 1/8") x w93mm (3 11/16") x D53mm (2 1/16")
Power Supply	26.6 Li-Ion
Battery Capacity	2950 mAh
Battery Life	Single Charge lasts 9 months
Noise	< 44 dBA
Max Length	10m (33')
Max Weight	45kg (99lb)
Control	RTS

RTS Motor	Battery Powered
	Wire free
	Built in radio receiver
	Controlled with Somfy remote or app control options / automation systems via RTS
	Compatible with Situio remote controls and TaHoma Switch



MOTOR FEATURES	Irismo 45WF RTS
Soft Start	✓
Soft Stop	✓
Intermediate Position	✓
Manual Override	✓
Touch Motion	✓
Automatic Limits on End Stop	✓
Back Release	✗
Adjustable Limits	✓
Speed Control & Adjustment	✓
Set via 3 NO Dry Contact Setting tool	✗
Setting with button on motor	✗
Motor direction change	✓
DCT ergonomics setting 2 or 3 buttons	✗
Factory reset	✓
LED indicators	✓
Modulability	✗
Silent mode	✗
Buzzer indicators	✓
Remote control	✓
App control	✓
Zigbee Integration	✗

⚡ MOVELITE 35 MOTOR WT • RTS

Size L265mm (10⁷/₁₆"") x w93mm (3¹¹/₁₆"") x d53mm (2¹/₁₆"")
Power Supply 90 - 255V, 50/60 Hz
Noise < 41 dBA
Max Length 6m (19.5')
Max Weight 35kg (77lb)
Control WT, RTS

WT Motor 4 core cable
 Mains switching
 Controlled with automation systems or hard wired wall switch

RTS Motor 3 core cable
 Built in radio receiver
 Dry contact, Volt free switching
 Controlled with Somfy remote or app control options / automation systems via volt free or RTS / volt free hard wired wall switch
 Compatible with Situo remote controls and TaHoma Switch



MOTOR FEATURES	Movelite 35 WT	Movelite 35 RTS
Soft Start	✗	✗
Soft Stop	✗	✗
Intermediate Position	✓	✓
Manual Override	✓	✓
Touch Motion	✓	✓
Automatic Limits on End Stop	✓	✓
Back Release	✗	✗
Adjustable Limits	✓	✓
Speed Control & Adjustment	✗	✗
Set via 3 NO Dry Contact Setting tool	✓	✓
Setting with button on motor	✗	✗
Motor direction change	✓	✓
DCT ergonomics setting 2 or 3 buttons	✓	✓
Factory reset	✓	✓
LED indicators	✗	✗
Modulability	✗	✗
Silent mode	✗	✗
Buzzer indicators	✗	✗
Remote control	✗	✓
App control	✗	✓
Zigbee Integration	✗	✗

MOVELITE 35 WF MOTOR RTS

Size	L279mm (10 ⁵ / ₁₆ ") x w93mm (3 ¹¹ / ₁₆ ") x D53mm (2 ¹ / ₁₆ ")
Power Supply	14.8 Li-Ion
Battery Capacity	2000 mAh
Battery Life	Single Charge lasts 4-6 months
Noise	< 41 dBA
Max Length	6m (19.5')
Max Weight	35kg (77lb)
Control	RTS

RTS Motor	Battery Powered
	Wire free
	Built in radio receiver
	Controlled with Somfy remote or app control options / automation systems via RTS
	Compatible with Situo remote controls and TaHoma Switch



MOTOR FEATURES	Movelite 35WF RTS
Soft Start	✗
Soft Stop	✗
Intermediate Position	✓
Manual Override	✓
Touch Motion	✓
Automatic Limits on End Stop	✓
Back Release	✗
Adjustable Limits	✓
Speed Control & Adjustment	✗
Set via 3 NO Dry Contact Setting tool	✗
Setting with button on motor	✗
Motor direction change	✓
DCT ergonomics setting 2 or 3 buttons	✗
Factory reset	✓
LED indicators	✓
Modulability	✗
Silent mode	✗
Buzzer indicators	✗
Remote control	✓
App control	✓
Zigbee Integration	✗

REMOTE CONTROL

Single channel remote can control one motor or a group of motors at the same time. If you require each motor to run independently then either Single channel remote must be specified for each window or a multi channel remote needs to be specified

Multi channel remote can control multiple motors independently or grouped together.

Compatible with RTS and Zigbee Options



APP CONTROL

The system can be controlled with the Somfy Tahoma app or through smart devices & Amazon Alexa.

The system can also be integrated with all major home control systems.

Compatible with RTS and Zigbee Options



AUTOMATION SYSTEMS

The system can also be integrated with all major home control systems.

This will require additional components and the system being installed & composing by automaton specialists





! Requires the motor to either have RTS built in or RTS module through a control system.

Single channel remote can control one motor or a group of motors at the same time.
Multi channel remote can control multiple motors independently or grouped together.


Situo 1 RTS - Single Channel Remote

Size	145 x 49 x 22 mm
Water Rating	IP 30
Battery Type	2430 Lithium - 3V
Channel	1
Frequency	433.42 MHz
Control	RTS
Range	200m in open field or 20m through 2 reinforce concrete walls
Colour	White
Misc	Wall holder included

Situo 5 RTS - Multi Channel Remote

Size	145 x 49 x 22 mm
Water Rating	IP 30
Battery Type	2430 Lithium - 3V
Channel	5
Frequency	433.42 MHz
Control	RTS
Range	200m in open field or 20m through 2 reinforce concrete walls
Colour	White
Misc	Wall holder included



 **Compatible with Glydea Ultra 60e motor with Zigbee module**

Single channel remote can control one motor or a group of motors at the same time.
 Multi channel remote can control multiple motors independently or grouped together.



YSIA 1 ZIGBEE - Single Channel Remote

Size	135 x 42 x 17 mm
Battery Type	2X AAA
Channel	1
Frequency	2.4 GHz
Control	Zigbee 3.0
Range	50m in open field
Colour	White
Misc	Wall holder included

YSIA 5 ZIGBEE - Multi Channel Remote

Size	135 x 42 x 17 mm
Battery Type	2X AAA
Channel	5
Frequency	2.4 GHz
Control	Zigbee 3.0
Range	50m in open field
Colour	White
Misc	Wall holder included



Requires the motor to either have RTS built in or RTS module through a control system.
Compatible with Glydea Ultra 60e motor with Zigbee module

From smart application to home automation, the most complete & evolutive connected experience with the TaHoma environment

- From the touch of a button, to app control, all the way to voice control, TaHoma switch offers an accessible to all and scalable smart home solution.
- Tahoma switch controls key home equipment from Somfy and major partner brands (shades, shutters, doors, gates, windows, heating, lighting, cameras, alarm systems and more) for more security, greater energy efficiency and enhanced comfort every day.
- Thanks to the native integration of the io-homecontrol, RTS and Zigbee 3.0 protocols along with cloud compatibilities Tahoma switch is an evolutive solution, that allows people to add equipment as they'd like.
- TaHoma switch is also compatible with Google Assistant and Amazon Alexa enlarging the user experience to voice control.

Tahoma

Radio frequency	868-870 MHz and 433.42 MHz
Technology	io-homecontrol, RTS and Zigbee 3.0
Connections§	1 x Micro-USB
Current	230 V / 5V DC 1 A
Enclosure class	IP30
Range	200 meters open field
Working temperature	0 ° C to + 50 ° C
Dimensions	162 x 67.5 x 34 mm
Weight	213 g
Colour	White
Location	Indoor
Other	LED (red / green / orange / white).
Miscellaneous	Two physical control buttons at the top of scenes.

CONTACT

www.bradleycollection.com



UK & REST OF THE WORLD

☎ +44 (0)1449 722 724

✉ info@bradleycollection.com

USA & CANADA

☎ +1 (310) 815 8255

✉ info.us@bradleycollection.com

LONDON SHOWROOM

☎ +44 (0)207 871 7793

✉ showroom@studiotwochelsea.com

THE BRADLEY COLLECTION



CEDIA
MEMBER

Specialised fixings for mounting brackets will be required in certain situations and are not provided as standard. Steel items are not recommended for damp conditions such as shower rooms. Crystal finials should not be positioned in direct sunlight, and are not suitable for use in conservatories.

The Bradley Collection reserves the right to modify design and materials without prior notice as part of a process of continual product improvement. Due to printing limitations, colours in this brochure may not be accurate.

Products are protected by Design Rights, under provisions of Copyright, Designs & Patents Act 1988. Bradley® and The Bradley Collection® are registered Community trademarks of The Bradley Collection Ltd. in Europe and registered trademarks of the Bradley Collection, Inc. in the USA. Gliderpole is a registered trademark of The Bradley Collection Ltd in the UK.

The Bradley Collection Ltd Lion Barn • Maitland Road • Needham Market • Suffolk • IP6 8NS • UK
The Bradley Collection Inc 10866 Washington Blvd #1275 • Culver City • CA 90232 • USA

Published: 0426 • Copyright © The Bradley Collection Ltd. 2026